	© Cop	terial Compo pyright 2005. IPC, Bannoc ternational and Pan-Americ	kburn, Illinois	. All rights reserv	tion with lower	level p	arts, the	declaratic	on encor		wer level mate	erials for	which t	e item is an assembly he manufacturer has declaration.		
1/32-2 1.1		Veb Site for Informat //www.ipc.org/IPC-1	-1752 Standa	rd					claration Class * ss 6 - RoHS Yes/No, Homogeneous Materials and Mfg Informa							
Supplier Information																
Company Name *	-	Company Unique ID		Unique ID Au	Response Date *				Response Do							
SEMTECH CORPORATION SEMTECH CORPOR			RATION			2017-02-23										
Contact Name * Title - Contact				Phone - Contact *			- Contac	t *				<b>A</b>				
Jeffrey Gabrielson QA Customer Service			e Specialis	cialis <b>805-498-2111</b>			jgabrielson@semtech.com			Duplicat	e Contact	-> Autho	orized Re	epresentative		
Authorized Representative * Title - Representative			Э	Phone - Representative *			Email - Representative *			Supplier Comments or URL for Additional Information						
Jeffrey Gabrielson QA Customer Ser			e Specialis	Specialis <b>805-498-2111</b>			jgabrielson@semtech.com									
Requester Item Number		Mfr Item Number		Mfr Item Name	Effectiv	ective Date Version Mar		Manufa	acturing Site	Weight *	UC	M	Unit Type			
	:	SC419ULTRT		EcoSpeed DC-DC Buck Contro						Malaysia		1085 mg		Each		
Alternate Recommenda	ation				Alternate Item			Item Co	Comments							
Manufacturing Proces	s Inf	ormation														
Terminal Plating / Grid Array N	/lateria	al	Terminal Ba	ase Alloy	J-STD-020 MSL Ra	ating	Peak Proc	ess Body	Temper	rature Max Tim	e at Peak Tem	perature	Number	of Reflow Cycles		
Matte Tin (Sn) CU Alloy Comments				260			<b>260</b> C	;	<b>30</b> se	econds	3					
SC419ULTRT is REACH-o	comp	oliant product, per E	EU Regula	tion EC1907/	2006 to include r	ecent a	addition o	of SVHC	candic	late list of su	bstances in	January	2017			

Save the fields in this form to a file	Evport Data	Import fields from a file into this form	Import Data	Clear all of the fields on this form	Reset Form	Lock the fields on this form to prevent chan	Look Cupplier Fields				
RoHS Material Composition Declaration Declaration Declaration Type * Detailed											
		ty limit of 0.1% by mass (100 Ethers (PBDE) and quantity					ominated Biphenyls (PBB),				
chromium, polybromina excess of an applicable gathered the information Company will rely on thi completing this form, ar certifications regarding conditions of that agree	ted biphenyls and/or polybrominate quantity limit, please indicate below it provides in this form using app s certification in determining the co d that Supplier may not have inde heir contributions to the part, and ment, including any warranty rights	ompliance of its products with European pendently verified such information. Ho those certifications are at least as comp	ricted substance?) in excess believe may apply. If the p y and that such information n Union member state laws owever, in situations where prehensive as the certificati hat agreement, will be the s	ss of the applicable quantity lim part is an assembly with lower I is true and correct to the best of that implement the RoHS Dire Supplier has not independently ion in this paragraph. If the Co sole and exclusive source of the	it identified above. If a homoge evel components, the declaration of its knowledge and belief, as of ctive. Company acknowledges y verified information provided lo popany and the Supplier enter is a Supplier?s liability and the Co	eneous material within the part cor on shall encompass all such comp of the date that Supplier complete: s that Supplier may have relied on by others, Supplier agrees that, at into a written agreement with resp impany?s remedies for issues that	ntains a RoHS restricted substance in ponents. Supplier certifies that it s this form. Supplier acknowledges that information provided by others in a minimum, its suppliers have provided				
RoHS Declaration	n * 1 - Item(s) does not conta	ain RoHS restricted substances per the	he definition above			Supplier Acceptance *	Accepted				
	e declared item does not co all applicable exemptions.	ntain RoHS restricted substanc	es per the definition a	above except for defined	RoHS exemptions, then	select the corresponding re	esponse in the RoHS Declaration				
Declaration S	ignature										
In a family of the second	ward a factor and the factor of the second s	al Calaba and all manages of the last		a second se		and the second s	town - town				

Instructions: Complete all of the required fields on all pages of this form. Select the "Accepted" on the Supplier Acceptance drop-down. This will display the signature area. Digitally sign the declaration (if required by the Requester) and click on Submit Form to have the form returned to the Requester.

Supplier Digital Signature

## Homogeneous Material Composition Declaration for Electronic Products

**Subltem Instructions:** The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Line Functions: +I Inserts a New Item /SubItem +M Inserts a new Material +C Inserts a new Substance Category +S Inserts a new Substance - Deletes the element line

	Item/SubItem		Homogeneous		Unit of		Level	Substance Category			Substance	CAS	Exempt	Weight		Tolerance		PPM
	Name		Material	weight	Measure		Level	Substance Category			Substance	CAS	Exempt	weight	Measure	-	+	
+  -	Lead frame	+M -M	Ag plated Cu C7	7.5487	mg	+C -C	Supplier		+S	-S	Cu	7440-50-8		7.36	mg			430,19
									+S	-S	Fe	7439-89-6		0.1774	mg			10,368
						+C -C	Supplier		+S	-S	Zn	7440-66-6		0.0091	mg			529.47
									+S	-S	Р	7723-14-0		0.0023	mg			132.37
									+S	-S	Ag	7440-22-4		0.06	mg			3,505.9
+I -I	Die	+M -M	Doped Silicon	1.2325	mg	+C -C	Supplier		+S	-S	Si	7440-21-3		1.2325	mg			72,041
+I -I	Die attach material	+M -M	Ablebond 8290	1.1529	mg	+C -C	Supplier		+S	-S	Ag	7440-22-4		0.8647	mg			50,542
	•		-						+S	-S	Epoxy Resin	Proprietary		0.1729	mg			10,108
									+S	-S	Amine	Proprietary		0.0461	mg			2,695.5
									+S	-S	Gamma Butyrolactone	96480		0.0346	mg			2,021.6
									+S	-S	Metal Oxide	Proprietary		0.0346	mg			2,021.6
+I -I	Wire bonding	+M -M	Gold	0.2038	mg	+C -C	Supplier		+S	-S	Au	7440-57-5		0.2037	mg			11,908
+I -I	Lead Finish	+M -M	Tin Alloy	0.4219	mg	+C -C	Supplier		+S	-S	Sn	7440-31-5		0.4219	mg			24,660
+I -I	Encapsulation	+M -M	Epoxy Resin EM	6.4887	mg	+C -C	Supplier		+S	-S	Silica Fused	60676-86-0		5.9502	mg			347,79
			<b></b>						+S	-S	Epoxy Resin	Proprietary		0.2595	mg			15,170
									+S	-S	Phenol Resin	Proprietary		0.2595	mg			15,170
									+S	-S	Carbon Black	1333-86-4		0.0195	mg			1,137.8